

# Clamp Meter

## MD 9260 TRMS Photovoltaic Clamp Meter CAT III 1500 V DC



The MD 9260 is the first Metrel instrument to support measurements up to 1500 V DC with CAT III safety. Its voltage range and safety make it useful in highly demanding environments like solar power plants, wind power plants, or other high power environment using DC current. It has 2000 A AC / DC current range and can additionally measure resistance, capacitance, frequency and temperature – in short a well-rounded multimeter-style tool for use in power applications.

### MEASUREMENT FUNCTIONS

- TRMS AC and DC voltage measurement;
- TRMS AC and DC current measurement;
- Capacitance measurement;
- Resistance measurement;
- Frequency measurement with VFD;
- Diode test;
- Temperature measurement;
- Acoustic continuity;
- Non-contact electrical field detection.

### KEY FUNCTIONS

- **1500 V DC range** with CAT III safety.
- **TRMS** for accurate measurement of sine and non-sine signals.
- **VFD**: low-pass filter for accurate frequency measurements of noisy signals.
- High current range of **2000 A**.
- **CAT III 1500 V DC** and **CAT IV 1000 V** safety
- Protection against **12 kV transients**.
- **Auto and manual** ranging.
- **Relative zero**: easily compare consecutive measurements.
- **Crest** function catches peaks as short as 5 ms.
- **Temperature** measurements up to 1000 °C.
- **PC connection** (optional): logging directly to a PC.

### APPLICATIONS

- Testing solar power systems up to 1500 V.
- Testing wind power systems.
- High level industrial testing.
- Testing of UPS and other large battery systems.

## TECHNICAL SPECIFICATION

| FUNCTION                            | RANGE                                    | ACCURACY                                                         |
|-------------------------------------|------------------------------------------|------------------------------------------------------------------|
| DC Voltage                          | 6.000 V ... 1500 V                       | ±(0.5 % of reading + 5 digits)                                   |
| AC Voltage (50 Hz ... 400 Hz)       | 6.000 V ... 1000 V                       | ±(1.2 % of reading + 5 digits)                                   |
| AC+DC Voltage (DC, 50Hz ... 400 Hz) | 6.000 V ... 1000 V                       | ±(1.4 % of reading + 7 digits)                                   |
| Variable Frequency Drive AC         | 10 Hz ... 400 Hz                         | ±(4.0 % of reading + 80 digits)                                  |
| DC Current                          | 200.0 A ... 2000 A                       | ±(2.0 % of reading + 5 digits)                                   |
| AC Current (50 Hz ... 400 Hz)       | 200.0 A ... 2000 A                       | ±(2.0 % of reading + 5 digits)                                   |
| Resistance                          | 600.0 Ω ... 40.00 MΩ                     | ±(0.5 % of reading + 5 digits)                                   |
| Capacitance                         | 60.00 nF ... 2000 μF                     | ±(2.0 % of reading + 5 digits)                                   |
| Temperature                         | -50 °C ... 1000 °C<br>-58 °F ... 1832 °F | ±(0.3 % of reading + 4 digits)<br>±(0.3 % of reading + 6 digits) |
| Mains frequency                     | 10 Hz ... 1999 Hz                        | ±(0.1 % of reading + 4 digits)                                   |
| Diode Test                          | 1.000 V                                  | ±(1.0 % of reading + 3 digit)                                    |
| Power supply                        | 2 x 1.5 V batteries, type AA             |                                                                  |
| Oversupply category                 | CAT IV / 1000 V, CAT III 1500 V          |                                                                  |
| Dimensions                          | 264 x 97 x 43 mm                         |                                                                  |
| Weight                              | 608 g                                    |                                                                  |

## GENERAL SPECIFICATION

|                          |                                                                                                                                                                                                                 |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display                  | 3-5/6 digits 6000 counts<br>3-1/2 digits 1,999 counts for Hz                                                                                                                                                    |
| Update Rate              | 5 per second nominal                                                                                                                                                                                            |
| Operating Temperature    | 0 °C ... 40 °C                                                                                                                                                                                                  |
| Relative Humidity        | Maximum relative humidity 80 % for temperature up to 31 °C decreasing linearly to 50 % relative humidity at 40 °C                                                                                               |
| Storage Temperature      | -20 °C ... 60 °C, < 80 % R.H. (with battery removed)                                                                                                                                                            |
| Altitude                 | Operating below 2000 m                                                                                                                                                                                          |
| Temperature Coefficient  | nominal 0.15 x (specified accuracy) / °C @ (0°C -18°C or 28°C -40°C), or otherwise specified                                                                                                                    |
| Sensing                  | True RMS                                                                                                                                                                                                        |
| Safety                   | IEC/EN/BSEN/CSA_C22.2_No./UL 61010-1 Ed. 3.1, 61010-2-032 Ed. 4.0 to measurement categories CAT IV 1000 V                                                                                                       |
| Transient Protection     | 12 kV (1.2/50 µs surge)                                                                                                                                                                                         |
| Overload Protections:    |                                                                                                                                                                                                                 |
| - Clamp-on jaws          | 2000 A rms continuous                                                                                                                                                                                           |
| - Voltage on terminals   | 1650 V DC / 1100 V AC rms                                                                                                                                                                                       |
| - Other functions        | 1500 V DC / 1000 V AC rms                                                                                                                                                                                       |
| E.M.C.:                  | Meets EN61326-1:2006                                                                                                                                                                                            |
| - In an RF field of 3V/m | Capacitance function is not specified                                                                                                                                                                           |
| - Other function ranges  | Total Accuracy = Specified Accuracy + 200 digits                                                                                                                                                                |
| - Performance above 3V/m | not specified                                                                                                                                                                                                   |
| Power Supply             | 1.5 V AA Size (IEC LR6) battery X 2                                                                                                                                                                             |
| Power Consumption        | Typical 14 mA for Current functions, and 5.2 mA for others                                                                                                                                                      |
| Low Battery              | Below approx. 2.4 V                                                                                                                                                                                             |
| APO Timing               | Idle for 34 minutes                                                                                                                                                                                             |
| APO Consumption          | 10 µA typical                                                                                                                                                                                                   |
| Jaw opening              | 55 mm max                                                                                                                                                                                                       |
| Special Features         | AutoCheckTM V&Ω; VFD-V & VFD-Hz; Backlighted LCD; 5 ms CREST-MAX Capture mode (Peak Hold); Auto-ranging Relative-Zero mode; Display Hold; EF-Detection (NCV); Optional Interface capabilities with PC computers |

## METREL D.D.

Measuring and Regulation Equipment

Manufacturer

Ljubljanska 77, SI-1354 Horjul, Slovenia

T +386 (0)175 58 200, F +386 (0)175 49 226

metrel@metrel.si, www.metrel.si

## ORDERING INFORMATION



### Standard set MD 9260

- MD 9260 TRMS Photovoltaic Clamp Meter CAT III 1500 V DC
- AMD 9026 Test lead with probe, 2 pcs
- AMD 9023 Thermocouple probe type K
- 1.5 V AA battery, 2 pcs
- Soft carrying pouch
- User manual

## OPTIONAL ACCESSORIES

| Photo | Order No. | Acc. description                        |
|-------|-----------|-----------------------------------------|
|       | AMD 9026  | Test lead with probe, 2 pcs             |
|       | AMD 9023  | Thermocouple probe, type K              |
|       | AMD 9024  | Adapter for thermocouple probe AMD 9023 |