

3310G Series

DC Electronic Load 75W~400W



DC ELECTRONIC LOAD



PRODIGIT ELECTRONICS CO., LTD.

No. 7-1, Zhongxing Rd., Tucheng Dist., New Taipei City 236, Taiwan (R.O.C.)

TEL : 886-2-2918-2620

FAX : 886-2-2912-9870

[http : //www.prodigit.com](http://www.prodigit.com)

E-mail : sales@prodigit.com.tw



3310G Series DC Electronic Load

	Normal mode		Turbo mode
3310G	60V / 30A / 150W	➔	60V / 60A / 300W
3311G	60V / 60A / 300W	➔	60V / 120A / 600W
3312G	250V / 12A / 300W	➔	250V / 24A / 600W
3314G	500V / 12A / 300W	➔	500V / 24A / 600W
3315G	60V / 15A / 75W	➔	60V / 30A / 150W
3316G	80V / 80A / 400W	➔	80V / 160A / 800W
3318G	500V / 20A / 400W	➔	500V / 40A / 800W



Features

- 5 digital V / A / W Meter can be displayed on Large LCD display simultaneously.
- Flexible CC, CR, CV, CP, CC + CV, CP + CV, Dynamic and short circuit operation modes.
- Built-in test modes include Battery Discharge, BMS, Fuse/Breaker Trip/Non-Trip, Short circuit, OCP, OPP test modes.
- Not only CC, CR, and CP mode have parallel operation functions, but CV mode also has parallel operation functions.
- Turbo mode can withstand up to 2 times the current and power electronic load within 2 sec. period, most fit Fuse/Breaker and BMS, Short circuit, OCP, OPP test.
- Provide battery BMS protection test function.
- High Slew Rate : 3310G up to 5A/uS, 3311G up to 10A/uS, 3315G up to 2.5A/uS
- Support MPPT CC, CR, CV test function for solar panel.
- Short circuit duration can be set within short circuit test.
- Can set the power-on status value.
- Voltage meter display can be configured as polarity positive ("+") or negative ("-").
- Synchronous parallel execution function (SYNC. Load on)
- Can be configured in the Mainframe of 3302G (single channel), 3305G (dual channels) or 3300G (Quad channels), each mainframe has up to 150 sets Store/Recall memory.
- Optional programmable NTC Resistor (installed in mainframe)
- Optional Interface : GPIB, RS232, USB, LAN.
- Protection against V, I, W, and °C.
- Optional 9923 load current waveform generator to provide the battery actual discharge current waveform simulation.

Descriptions

- Each 3310G Series module has its own control and display panel, CC/CR/CV/CP/Dynamic modes, plug in 3302G/3305G/3300G mainframe with 150 sets Store/Recall memory which provides load set-up more efficiently, also can be controlled via RS232, Ethernet, USB and GPIB interface.
- The new Turbo mode is designed for overload or protection testing, which includes OCP, OPP, Short for AC/DC or DC/DC power source; Over Charge/Discharge and Short for Battery BMS protection; and Blow/Not Blow testing for Fuse, Breaker or PTC Current Protection Components.
- Support Short, OCCP and OCDP protection tests for battery BMS protection testing, the peak current before protection and protection response time are measured.
- BMS, Fuse, OCP and OPP single-key test functions on the module make test more efficient.
- Dynamic can be simulated under CC, CP mode. The current Rise / Fall slew rate can be adjusted individually and there is an external signal input so that load can have a simulated Specific Load Current Waveform, optional 9923 Load Current Waveform Generator is able to support real current waveform testing.
- SHORT duration setting and SHORT_VH, SHORT_VL setting function, also can measure Short Voltage and Current.
- Programmable LOAD ON/OFF voltage, GO/NG meter check, Voltage meter display "+" or "-" is selectable and 150 sets Store / Recall larger memory is much advance feature for each different application.
- 150 sets test parameter and status storage function can call the storage memory real time in accordance with the auto sequence requirement, at any time to tune out the stored memory for use.

Applications

- Voltage / Current source
- SMPS transient response
- Voltage Source Current limit testing and battery emulation for Charger testing
- Battery discharge capacity
- Lithium battery BMS charge and discharge protection
- Fuse, Breaker, PTC specification test
- MPPT test function for solar panels
- R&D, Quality Control
- ATE system
- Production testing

Specifications

MODEL	3310G		3311G		3312G	
Power	150W, 300W max. ^{*1}		300W, 600W max. ^{*1}		300W, 600W max. ^{*1}	
Current	30A, 60A max. ^{*1}		60A, 120A max. ^{*1}		12A, 24A max. ^{*1}	
Voltage	60V		60V		250V	
Min. Operating Voltage	0.3V @ 30A		0.3V @ 60A		1V @ 12A	
PROTECTIONS						
Over Power Protection (OPP)			105%			
Over Current Protection (OCP)			105%			
Over Voltage Protection (OVP)			105%			
Over Temp Protection (OTP)			YES			
Constant Current Mode						
Range ^{*2}	0 ~ 3A	0 ~ 30A	0 ~ 6A	0 ~ 60A	0 ~ 1.2A	0 ~ 12A
Resolution	0.05mA	0.5mA	0.1mA	1mA	0.02mA	0.2mA
Accuracy ^{*3}	± 0.05% of (Setting + Range)					
Constant Resistance Mode						
Range	2~120KΩ	0.02Ω~2Ω	1Ω~60 KΩ	0.0083Ω~1Ω	25Ω~1500KΩ	0.08Ω~25Ω
Resolution	0.00833mS	0.033mΩ	0.0166mS	0.0166mΩ	0.00066mS	0.4166mΩ
Accuracy	± 0.2% of (Setting + Range)					
Constant Voltage Mode						
Range	0 ~ 6V	0 ~ 60V	0 ~ 6V	0 ~ 60V	0 ~ 30V	0 ~ 250V
Resolution	0.0001V	0.001V	0.0001V	0.001V	0.001V	0.01V
Accuracy	± 0.025% of (Setting + Range)					
Constant Power Mode						
Range	0 ~ 15W	0 ~ 150W	0 ~ 30W	0 ~ 300W	0 ~ 30W	0 ~ 300W
Resolution	0.00025W	0.0025W	0.0005W	0.005W	0.0005W	0.005W
Accuracy ^{*4}	± 0.1% of (Setting + Range)					
Constant Voltage + Current Limit Mode						
Range	60V	30A	60V	60A	250V	12A
Resolution	0.001V	0.5mA	0.001V	1mA	0.01V	0.2mA
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Constant Voltage + Power Limit Mode						
Range	60V	150W	60V	300W	250V	300W
Resolution	0.001V	0.0025W	0.001V	0.005W	0.01V	0.005W
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Turbo mode ^{*1}						
Short/OCP/OPP Test Function						
Maximum Current	30A	60A	60A	120A	12A	24A
Meas. Accuracy	± 1.0% of (Reading + Range)					
Short time	100ms~10 Sec. or Continue	100~2000mS	100ms~10 Sec. or Continue	100~2000mS	100ms~10 Sec. or Continue	100~2000mS
Meas. Accuracy	NA	NA	NA	NA	NA	NA
OCP Time (Tstep)	100mS	20mS	100mS	20mS	100mS	20mS
Meas. Accuracy	NA	NA	NA	NA	NA	NA
OPP Time (Tstep)	100mS	20mS	100mS	20mS	100mS	20mS
Meas. Accuracy	NA	NA	NA	NA	NA	NA
Turbo mode ^{*5}						
	OFF	ON	OFF	ON	OFF	ON
Short time	100ms~10 Sec. or Continue	0.05mS~10ms	100~1000ms	0.05mS~10ms	100ms~10 Sec. or Continue	0.05mS~10ms
Meas. Accuracy	NA	±0.005mS	NA	±0.005mS	NA	±0.005mS
OCP Time (Tstep)	100mS	0.05mS~10mS / 11~1000mS	20mS	0.05mS~10mS / 11~1000mS	100mS	0.05mS~10mS / 11~1000mS
Meas. Accuracy	NA	±0.005mS / ±0.2mS	NA	±0.005mS / ±0.2mS	NA	±0.005mS / ±0.2mS
Fuse Test Mode ^{*6}						
Trip & Non-Trip Time	1~5999ms, 6~16383sec	1~2000mS	1~5999ms, 6~16383sec	1~2000mS	1~5999ms, 6~16383sec	1~2000mS
Meas. Accuracy	± 0.04mS (<200mS) , ± 20mS (>200mS)					
Repeat Time	0~255					
Surge Test Mode						
Surge current	0~60A		0~120A		0~24A	
Normal current	0~30A		0~60A		0~12A	
Surge Time	10~2000ms					
Surge Step	1~5					
MPPT Mode						
Algorithm	P & O					
Load mode	CV					
P&O interval	1000ms ~ 60000ms					
Resolution	1000mS					
Dynamic Mode (50KHz)						
Timing						
Thigh & Tlow	0.010~9.999 / 99.99 / 999.9 / 9999mS					
Resolution	0.001 / 0.01 / 0.1 / 1mS					
Slew rate	0.008 ~ 0.5A/μS	0.08 ~ 5A/μS	0.016 ~ 1A/μS	0.16 ~ 10A/μS	0.0008 ~ 0.05A/μS	0.008 ~ 0.5A/μS
Accuracy	± (5% of Setting) ±10μS					
Measurement						
Voltage Read Back						
Range (5 Digital)	6V	60V	6V	60V	30V	250V
Resolution	0.0001V	0.001V	0.0001V	0.001V	0.001V	0.01V
Accuracy	± 0.025% of (Reading + Range)					
Current Read Back						
Range (5 Digital)	3A	30A	6A	60A	1.2A	12A
Resolution	0.0001A	0.001A	0.0001A	0.001A	0.00002A	0.0002A
Accuracy	± 0.05% of (Reading + Range)					
Power Read Back						
Range (5 Digital)	15W	150W	30W	300W	30W	300W
Resolution	0.0001W	0.001W	0.001W	0.01W	0.001W	0.01W
Accuracy ^{*7}	± 0.125% of (Reading + Range)					
Current Monitor	FULL SCALE 10V					
Accuracy	0.5% of (Setting + Range)					
Current Programming Input	FULL SCALE 10V					
Programmable Short	BUILT-IN					
Load ON Voltage	0.1 ~ 25V		0.1 ~ 25V		0.2 ~ 50V	
Accuracy	1% of (Setting + Range)					
Load OFF Voltage	0 ~ 25V		0 ~ 25V		0 ~ 50V	
Accuracy	0.025% of (Setting + Range)					
Typical Short Resistance (Cont.)	0.0166Ω		0.0083 Ω		0.08 Ω	
Max. Short Current (Cont.)	30A		60A		12A	
Dimension (HxWxD)	143 x 108 x 412 mm					
Operating Temperature ^{*8}	0 ~ 40℃					

*1 Turbo mode for up to 2X Current rating & Power rating support Fuse, BMS, Short/OCP/OPP test function

*2 The range is automatically or forcing to range II only in CC mode

*3 If the operating current is below range 0.1%, the accuracy specification is 0.1% F.S.

*4 If the operating power below range 2%, the accuracy specification is 0.2% of setting + range.

*5 BMS Test function for Battery Management System Board SHORT, OCCP and OCPD Test

*6 Fuse Test function for Fuse and Breaker test

*7 Power range = Vrange F.S. x Irange F.S.

*8 Operating temperature range is 0~40°C, all specification apply for 25°C±5°C, Except as noted

Order Information

DC Electronic Load

- **3310G** 60V , 30A , 150W
- **3311G** 60V , 60A , 300W
- **3312G** 250V , 12A , 300W



DC Electronic Load Mainframe

- **3302G** (single channel mainframe)
5.5kg / W160mm / H177mm / D452mm



Optional interface : ① GPIB Card ② RS232 Card ③ USB Card ④ LAN Card

- **3305G** (two channels mainframe)
7.5kg / W269mm / H177mm / D452mm



- **3300G** (four channels mainframe)
9.3kg / W440mm / H177mm / D445mm



High Slew Rate
3310G ▶ 5A/μS
3311G ▶ 10A/μS
3315G ▶ 2.5A/μS

Optional feature : NTC Simulator ① 10KΩ NTC(100~500KΩ) ② 100KΩ NTC (1000~5MΩ)

All specifications are subject to change without notice.

MODEL									
Power		3314G				3315G			
Current		300W, 600W max. *1				75W, 150W max. *1			
Voltage		12A, 24A max. *1				15A, 30A max. *1			
Min. Operating Voltage		500V				60V			
		6V @ 12A				0.25V @ 15A			
PROTECTIONS									
Over Power Protection (OPP)						105%			
Over Current Protection (OCP)						105%			
Over Voltage Protection (OVP)						105%			
Over Temp Protection (OTP)						YES			
Constant Current Mode									
Range *2		0 ~ 1.2A		0 ~ 12A		0 ~ 1.5A		0 ~ 15A	
Resolution		0.02mA		0.2mA		0.0254mA		0.25mA	
Accuracy *3		± 0.05% of (Setting + Range)							
Constant Resistance Mode									
Range		50 ~ 3000KΩ		0.5Ω ~ 50Ω		4Ω ~ 240 KΩ		0.02Ω ~ 4Ω	
Resolution		0.000333mS		0.8333mΩ		0.04166mS		0.0666mΩ	
Accuracy		± 0.2% of (Setting + Range)							
Constant Voltage Mode									
Range		0 ~ 60V		0 ~ 60V		0 ~ 6V		0 ~ 60V	
Resolution		0.001V		0.001V		0.0001V		0.001V	
Accuracy		± 0.025% of (Setting + Range)							
Constant Power Mode									
Range		0 ~ 30W		0 ~ 300W		0 ~ 7.5W		0 ~ 75W	
Resolution		0.001W		0.01W		0.000125W		0.00125W	
Accuracy *4		± 0.1% of (Setting + Range)							
Constant Voltage + Current Limit Mode									
Range		500V		12A		60V		15A	
Resolution		0.01V		0.2mA		0.001V		0.25mA	
Accuracy		±0.05% of (Setting+Range)		±1.0% of (Setting+Range)		±0.05% of (Setting+Range)		±1.0% of (Setting+Range)	
Constant Voltage + Power Limit Mode									
Range		500V		300W		60V		75W	
Resolution		0.01V		0.01W		0.001V		0.00125W	
Accuracy		±0.05% of (Setting+Range)		±1.0% of (Setting+Range)		±0.05% of (Setting+Range)		±1.0% of (Setting+Range)	
Turbo mode *1									
Short/OCP/OPP Test Function		OFF		ON		OFF		ON	
Maximum Current		12A		24A		15A		30A	
Meas. Accuracy		± 1.0% of (Reading + Range)							
Short time		100ms~10 Sec.		100~2000mS		100ms~10 Sec.		100~2000mS	
Meas. Accuracy		NA		NA		NA		NA	
OCP Time (Tstep)		100mS		20mS		100mS		20mS	
Meas. Accuracy		NA		NA		NA		NA	
OPP Time (Tstep)		100mS		20mS		100mS		20mS	
Meas. Accuracy		NA		NA		NA		NA	
Turbo mode *5									
		OFF	ON	OFF	ON	OFF	ON	OFF	ON
Short time		100ms~10 Sec. or Continue	0.05mS~10ms	100~1000ms	0.05mS~10ms	100ms~10 Sec. or Continue	0.05mS~10ms	100~1000ms	0.05mS~10ms
Meas. Accuracy		NA	±0.005mS	NA	±0.005mS	NA	±0.005mS	NA	±0.005mS
OCP Time (Tstep)		100mS	0.05mS~10mS / 11~1000mS	20mS	0.05mS~10mS / 11~1000mS	100mS	0.05mS~10mS / 11~1000mS	20mS	0.05mS~10mS / 11~1000mS
Meas. Accuracy		NA	±0.005mS / ±0.2mS	NA	±0.005mS / ±0.2mS	NA	±0.005mS / ±0.2mS	NA	±0.005mS / ±0.2mS
Fuse Test Mode *6									
Trip & Non-Trip Time		1~5999ms, 6~16383sec		1~2000mS		1~5999ms, 6~16383sec		1~2000mS	
Meas. Accuracy		± 0.04mS (<200mS) , ± 20mS (>200mS)							
Repeat Time		0~255							
Surge Test Mode									
Surge current		0~24A				0~30A			
Normal current		0~12A				0~15A			
Surge Time		10~2000ms							
Surge Step		1~5							
MPPT Mode									
Algorithm		P & O							
Load mode		CV							
P&O interval		1000ms ~ 60000ms							
Resolution		1000mS							
Dynamic Mode (50KHz)									
Timing									
Thigh & Tlow		0.010~9.999 / 99.99 / 999.9 / 9999mS							
Resolution		0.001 / 0.01 / 0.1 / 1mS							
Slew rate		0.0008 ~ 0.05A/μS		0.008 ~ 0.5A/μS		0.004 ~ 0.25A/μS		0.04 ~ 2.5A/μS	
Accuracy		± (5% of Setting) ±10μS							
Measurement									
Voltage Read Back									
Range (5 Digital)		60V		600V		6V		60V	
Resolution		0.001V		0.01V		0.0001V		0.001V	
Accuracy		± 0.025% of (Reading + Range)							
Current Read Back									
Range (5 Digital)		1.2A		30A		1.5A		15A	
Resolution		0.0001A		0.001A		0.00001A		0.001A	
Accuracy		± 0.05% of (Reading + Range)							
Power Read Back									
Range (5 Digital)		30W		300W		7.5W		75W	
Resolution		0.0001A		0.001A		0.0001W		0.001W	
Accuracy *7		± 0.1% of (Reading + Range)							
Current Monitor		FULL SCALE 10V							
Accuracy		0.5% of (Setting + Range)							
Current Programming Input		FULL SCALE 10V							
Programmable Short		BUILT-IN							
Load ON Voltage		0.4 ~ 100V				0.1 ~ 25V			
Accuracy		1% of (Setting + Range)							
Load OFF Voltage		0 ~ 100V				0 ~ 25V			
Accuracy		0.025% of (Setting + Range)							
Typical Short Resistance (Cont.)		0.5 Ω				0.02 Ω			
Max. Short Current (Cont.)		12A				15A			
Dimension (HxWxD)		143 x 108 x 412 mm							
Operating Temperature *8		0 ~ 40℃							

*1 Turbo mode for up to 2X Current rating & Power rating support Fuse, BMS, Short/OCP/OPP test function

*2 The range is automatically or forcing to range II only in CC mode

*3 If the operating current is below range 0.1%, the accuracy specification is 0.1% F.S.

*4 If the operating power below range 2%, the accuracy specification is 0.2% of setting + range.

*5 BMS Test function for Battery Management System Board SHORT, OCCP and OCDDP Test

*6 Fuse Test function for Fuse and Breaker test

*7 Power range = Vrange F.S. x Irange F.S.

*8 Operating temperature range is 0~40°C, all specification apply for 25°C±5°C, Except as noted

Order Information

DC Electronic Load

- 3314G 500V · 12A · 300W
- 3315G 60V · 15A · 75W



DC Electronic Load Mainframe

3302G
(single channel mainframe)
5.5kg / W160mm /
H177mm / D452mm



Optional interface : ❶ GPIB Card ❷ RS232 Card ❸ USB Card ❹ LAN Card

3305G
(two channels mainframe)
7.5kg / W269mm /
H177mm / D452mm



3300G
(four channels mainframe)
9.3kg / W440mm /
H177mm / D445mm



High Slew Rate
3310G ▶ 5A/μS
3311G ▶ 10A/μS
3315G ▶ 2.5A/μS

Optional feature : NTC Simulator ❶ 10KΩ NTC(100~500KΩ) ❷ 100KΩ NTC(1000~5MΩ)

Specifications

MODEL	3316G		3318G	
Power	400W, 800W max. ^{*1}		400W, 800W max. ^{*1}	
Current	80A /160A max. ^{*1}		20A / 40A max. ^{*1}	
Voltage	80V		500V	
Min. Operating Voltage	0.8V @ 80A		4V @ 20A	
PROTECTIONS				
Over Power Protection(OPP)			105%	
Over Current Protection(OCP)			105%	
Over Voltage Protection(OVP)			105%	
Over Temp Protection(OTP)			YES	
Constant Current Mode				
Range ^{*2}	0 ~ 8.04A	0 ~ 80A	0 ~ 2.04A	0 ~20A
Resolution	0.134mA	1.34mA	0.034mA	0.34mA
Accuracy ^{*3}	± 0.05% of (setting + Range)			
Constant Resistance Mode				
Range	1Ω~ 60KΩ	0.0083Ω ~ 1Ω	30Ω~ 1800KΩ	0.3Ω ~ 30Ω
Resolution	0.0166mS	0.0166mΩ	0.000555mS	0.5mΩ
Accuracy	± 0.2% of (Setting + Range)			
Constant Voltage Mode				
Range	0 ~ 8.04V	0 ~ 80V	60V	500V
Resolution	0.000134V	0.00134V	0.001V	0.01V
Accuracy	± 0.025% of (Setting + Range)			
Constant Power Mode				
Range	0 ~ 40.02W	0 ~ 400W	0 ~ 40.02W	0 ~ 400W
Resolution	0.667mW	6.67mW	0.667mW	6.67mW
Accuracy ^{*4}	± 0.1% of (Setting + Range)			
Constant Voltage + Current Limit Mode				
Range	80V	80A	500V	20A
Resolution	0.00134V	1.34mA	0.01V	0.34mA
Accuracy	± 0.05% of (Setting + Range)	± 1.0% of (Setting + Range)	± 0.05% of (Setting + Range)	± 1.0% of (Setting + Range)
Constant Voltage + Power Limit Mode				
Range	80V	400W	500V	400W
Resolution	0.00134V	6.67mW	0.01V	6.67mW
Accuracy	± 0.05% of (Setting + Range)	± 1.0% of (Setting + Range)	± 0.05% of (Setting + Range)	± 1.0% of (Setting + Range)
Turbo mode ^{*1}				
	OFF	ON	OFF	ON
Short/OCP/OPP Test Function				
Meas. Accuracy	± 3.0% of (Reading + Range)			
Maximum Current	80A	160A	20A	40A
Short Time	100ms~10 Sec. or Continue	100~2000ms	100ms~10 Sec. or Continue	100~2000ms
Meas. Accuracy	NA			
OCP Time (Tstep)	100ms	20ms	100ms	20ms
Meas. Accuracy	NA			
OPP Time (Tstep)	100ms	20ms	100ms	20ms
Meas. Accuracy	NA			
BMS Test Mode ^{*5}				
Short Time	0.05mS~10ms	0.05mS~10ms	0.05mS~10ms	0.05mS~10ms
Meas. Accuracy	±0.005mS			
OCP Time (Tstep)	0.05mS~10ms / 11~1000ms	0.05mS~10ms / 11~1000ms	0.05mS~10ms / 11~1000ms	0.05mS~10ms / 11~1000ms
Meas. Accuracy	±0.005mS / ±0.2mS			
Fuse Test Mode ^{*6}				
Trip & Non-Trip Time	r1:1~5999ms, r2:6~16383sec	1~2000mS	r1:1~5999ms, r2:6~16383sec	1~2000mS
Meas. Accuracy	r1 : ±0.2mS(<200mS), ±20mS(>200mS), r2: ±0.5S			
Repeat Cycle	0~255			
Surge Test Mode				
Surge current	0~160A		0~40A	
Normal current	0~80A		0~20A	
Surge Time	10~2000ms			
Surge Step	1~5			
MPPT Mode				
Algorithm	P&O			
Load mode	CV			
P&O interval	1000ms ~ 60000ms			
Resolution	1000ms			
Dynamic Mode (50KHz)				
Timing				
Thigh & Tlow	0.010~9.999 / 99.99 / 999.9 / 9999mS			
Resolution	0.001 / 0.01 / 0.1 / 1mS			
Slew rate	5.4 ~ 337.5mA/μs	54~ 3375mA/μs	1.28 ~ 80mA/μs	12.8 ~ 800mA/μs
Accuracy	± (5% of Setting) ±10μS			
Measurement				
Voltage Read Back				
Range (5 Digital)	8.04V	80V	60V	500V
Resolution	0.000134V	0.00134V	0.001V	0.01V
Accuracy	± 0.025% of (Reading + Range)			
Current Read Back				
Range (5 Digital)	8.04A	80A	2.1A	20A
Resolution	0.000134A	0.00134A	0.000034A	0.00034A
Accuracy	± 0.05% of (Reading + Range)			
Power Read Back				
Range (5 Digital)	400W		400W	
Resolution	0.01W		0.01W	
Accuracy ^{*7}	± 0.1% of (Reading + Range)			
Current Monitor	FULL SCALE 10V			
Accuracy	0.5% of (Setting + Range)			
Current Programming Input	FULL SCALE 10V			
Programmable Short	BUILT-IN			
Load ON Voltage	0.1 ~ 25V		0.4~100V	
Accuracy	1% of (Setting + Range)			
Load OFF Voltage	0 ~ 24.866V		0~99V	
Accuracy	0.025% of (Setting + Range)			
Typical Short Resistance	0.009Ω		0.15Ω	
Maximum Short Current	80A		20A	
Dimension(HxWxD)	143 x 108 x 412 mm			
Operating Temperature ^{*8}	0 ~ 40℃			

*1 Turbo mode for up to 2X Current rating & Power rating support Fuse, BMS, Short/OCP/OPP test function

*2 The range is automatically or forcing to range II only in CC mode

*3 If the operating current is below range 0.1%, the accuracy specification is 0.1% F.S.

*4 If the operating power below range 2%, the accuracy specification is 0.2% of setting + range.

*5 BMS Test function for Battery Management System Board SHORT, OCCP and OCPD Test

*6 Fuse Test function for Fuse and Breaker test

*7 Power range = Vrange F.S. x Irange F.S.

*8 Operating temperature range is 0~40°C, all specification apply for 25°C±5°C, Except as noted

Order Information

DC Electronic Load

- **3316G**
80V · 80A · 400W
- **3318G**
500V · 20A · 400W



DC Electronic Load Mainframe

Optional interface : ① GPIB Card ② RS232 Card ③ USB Card ④ LAN Card

3302G
(single channel mainframe)
5.5kg / W160mm /
H177mm / D452mm



3305G
(two channels mainframe)
7.5kg / W269mm /
H177mm / D452mm



3300G
(four channels mainframe)
9.3kg / W440mm /
H177mm / D445mm

