

LLT & PH3-LLT

Live Line Tester and Proving Unit



The Seaward LLT is ideal for live line testing on systems up to 1100V DC and is totally encapsulated in a high impact rugged enclosure with high visibility cable. The unit is fitted with high intensity red LED indicators and a polarizing filter making it clearly visible, even in direct sunlight. The PH3-LLT proving unit is ideal for proof testing before and after use supplied in a high visibility holster with belt clip.

The live line tester and proving unit are approved by Network Rail - Certificate of Acceptance No PA05/03345.

SPECIFICATIONS

LLT Live line tester

- Working Voltage 1100V DC max
- Threshold Voltage 200VAC/300VDC
- Circuit current <10mA
- Indicator 3 ultra-bright red LED
- Compliance BS EN61243-3

PH3-LLT Proving unit

- Output Voltage 500V DC nominal
- Output current 0.45mA into 2k Ω m
- Two non-touchable terminals
- Neon 'active' indicator
- Compliance BS EN61010-1

Carry case

- Carrying case with shoulder for LLT plus the PH3-LLT

Part numbers

- | | |
|------------------------|----------------|
| | 114A922 |
| ■ PH3-LLT proving unit | 112A925 |
| | 308A955 |



Web: www.seaward.co.uk **Email:** sales@seaward.co.uk

Seaward

Bracken Hill,
South West Industrial Estate,
Peterlee, SR8 2SW

Tel: +44 (0) 191 5863511

Fax: +44 (0) 191 5860227