

# **LMP 40**

Manual calibration handpump LMP 40. Range -950 mbar... 40 bar. Allows you to check an instrument simultaneously a precision instrument (Precision digital pressure gauge IKA 200). With comparison of the two measured values can be deduced accurately and thus make an adjustment and / or monitoring instrument. Thanks to a fine adjustment valve, it allows to reach the value measured accurately.

# **APPLICATIONS**



# **INCLUDES:**

Crimp connector for reference instrument female 1/4" NPT

Fine adjustment valve

Pressure relief valve

Mutation on the pressure / vacuum generation

Adjustable locknut for adjusting the delivery rate of the pump (overpressure protection)

Pressure connection for the test sample, female 1/4 "G, freely rotating

Flexible connection pipe test element (length 0.5m)



**Technical data** 

**Pressure range** -0.95 ... + 35.0 bar

**Medium** Air

Pressure connection Female ¼" NPT, ,tube with female G ¼", rota-

tes freely to DUT

Fine adjustment of pressure Fine adjustment valve

Overpressure connection Adjustable via locknut

Material Steel, chrome anodized aluminum, durable

plastic

**Dimensions** 220 (L) x 105 (W) x 63 (D) mm

Weight 0.51 kg

Standard accesories Evidence connection tube, 0.5 m long

# **INCLUDED IN THE SUPPLY**

Handpump LMP 40

Flexible tube with BSP 1/4" with free rotation

Reference manometer adapter NPT 1/4" (female)

# **OPTIONAL**

Carrying case bomb test

Dimensions in mm (W/H/D) 395 x 295 x 106

Set of adapters and seal assembly for connecting the test element  $\ G\ 1/8"$ ,  $\ G\ 3/8"$  and female  $\ 1/8"$ .

Set of adapters and seal assembly for connecting the test element G  $\frac{1}{4}$ " male to M12 x 1.5, M20 x 1.5 Minimess®

Set of adapters and seal assembly for connecting the test element G  $\frac{1}{2}$ " male to 1/8" NPT,  $\frac{1}{2}$ " NPT and female  $\frac{1}{2}$ " NPT

Service kit for hand pump test LMP 40 with several O-rings and seals

Precision digital pressure gauge IKA 200