

# SEFRAM INSTRUMENTS

## Digital Catalog



**Sefram**

- Phone : +33 (0)4 77 59 01 01
- Web : [www.sefram.com](http://www.sefram.com)
- E-mail : [sales@sefram.com](mailto:sales@sefram.com)

# Digital Catalogue

SEFRAM digital catalogue contains many hypertext links to aim at:

- Allowing you to quickly and easily choose your product,
- Guiding you on the products pages from our website to show you the associated accessories,
- Guiding you on the detailed technical documentations.

  
[Contents return](#)

## ➤ DATA ACQUISITION SOLUTIONS


○ A portable data acquisition solution for all your process applications.

  
**DAS 220**

  
**DAS 240**

Model	DAS 220	DAS 240
Number of channels	10 multiplexed channels	20 to 200 multiplexed channels
Touch screen	TFT 10 " Colour	TFT 10 " Colour
Measured values	Temperature, DC Voltage, Current, Resistance	Temperature, DC Voltage, Current, Resistance
Max. permissible Voltage	100 V DC	100 V DC
Max Sampling Frequency	1 kHz (1 ms)	1 KHz (1 ms)
Internal Memory	32 Go	32 Go
Battery life	15 h	15 h
External piloting and processing software	✓	✓
Interface	USB, Ethernet, Wi-Fi, Digital Input/Output	USB, Ethernet, Wi-Fi, Digital Input/Output
Detailed data sheet		

DAS220-240 DATA ACQUISITION

  
**Technical Documentation**


SEFRAM's website home page

Products page

Social networks

- **DATA ACQUISITION SOLUTIONS AND DATALOGGERS**
  -  Data Acquisition Solutions up to 200 channels ..... p.5
  - High-Speed Data Acquisition Solutions up to 6 channels ..... p.6
    - Bench Data Acquisition Solutions ..... p.7
    - Temperature Dataloggers ..... p.9
- **TV METERS**
  - Intuitive TV Meters ..... p.10
  - Professional TV meters ..... p.11
- **MULTIMETERS, CLAMPS AND VOLTAGE TESTER**
  - High Accuracy TRMS AC + DC Multimeters ..... p.12
  - TRMS AC Multimeters ..... p.13
  - Current Clamps ..... p.14
  - Power Meter Clamps ..... p.16
  - Voltage Testers ..... p.17
- **ELECTRICAL TESTERS**
  - Insulation testers ..... p.18
  - Earth testers ..... p.19
  - Cable tracers ..... p.20

- **ENVIRONMENT TESTERS**

- Thermometers, Thermo-hygrometer, Sonometer, Anemometer, Light meter, Thermography cameras ..... p.21


- **LABORATORY INSTRUMENTS**

- DC Power Supplies ..... p.24
- AC Power Sources ..... p.30
- AC+DC Power Sources ..... p.31
- DC Electronic Loads ..... p.32
- LCR Meters ..... p.36
- Bench Multimeters ..... p.38
- Functions Generators ..... p.39
- Digital oscilloscopes ..... p.42
- Spectrum Analysers, RF Power Meter and USB Peak RF sensors ..... p.43
- Battery Analyzers ..... p.46



# DATA ACQUISITION SOLUTIONS

A portable Data Acquisition Solution for all your process applications.



DAS220/DAS220BAT



DAS240/DAS240BAT

Model	DAS220/DAS220BAT	DAS240/DAS240BAT
Number of channels	10 multiplexed channels	20 to 200 multiplexed channels
Touchscreen	TFT 10 " Colour	TFT 10 " Colour
Measured values	Temperature, DC Voltage, Current, Resistance	Temperature, DC Voltage, Current, Resistance
Maximum Voltage	100 V DC	100 V DC
Max Sampling Frequency	1 kHz (1 ms)	1 kHz (1 ms)
Internal Memory	32 GB	32 GB
Battery life	15 h (with BAT option)	15 h (with BAT option)
Remote control and process software	✓	✓
Interface	USB, Ethernet, Wi-Fi, Digital Input/Output	USB, Ethernet, Wi-Fi, Digital Input/Output
Detailed datasheet		

DAS 220 / DAS 240





# DATA ACQUISITION SOLUTIONS

A portable, high-speed and multi-purposed Data Acquisition Solution with power analysis function\*.



DAS 30



DAS 50



DAS 60

\*Internal printer option available for each model

Model	DAS 30	DAS 50	DAS 60
Number of channels	2 isolated universal channels	4 isolated universal channels	6 isolated universal channels
Touchscreen	TFT 10" Colour	TFT 10" Colour	TFT 10 " Colour
Measured values	Temperature, DC Voltage / AC+DC, Current, Resistance, Frequency	Temperature, DC Voltage / AC+DC, Current, Resistance, Frequency	Temperature, DC Voltage / AC+DC, Current, Resistance, Frequency
Maximum Voltage	500 V	500 V	500 V
Bandwidth	100 kHz	100 kHz	100 kHz
Max Sampling Frequency	1 MHz (1 μs)	1 MHz (1 μs)	1 MHz (1 μs)
Power analysis	✓ (Up to 100Hz)	✓ (Up to 100Hz)	✓ (Up to 400 Hz)
Internal Memory	32 GB	32 GB	64 GB
Battery life	9h30	9h30	9h30
Remote control and process software	✓	✓	✓
Interface	USB, Ethernet, Wi-Fi, Digital Input/Output	USB, Ethernet, Wi-Fi, Digital Input/Output	USB, Ethernet, Wi-Fi, Digital Input/Output
Detailed datasheet			


DAS 30 / DAS 50 / DAS 60





# DATA ACQUISITION SOLUTIONS

Modular High Speed Data Acquisition Solution for all demanding applications.



DAS 1700



8460

Model	DAS 1700	8460
Number of channels	6 to 72 channels	6 to 36 channels (thermal printer)
Acquisition card type	Multiplexed, Universal, Strain gauge	Multiplexed, Universal, Strain gauge
Touchscreen	TFT 15.6 " Colour	TFT 15.4 " Colour
Measured values	Temperature, DC Voltage / AC+DC, Current, Resistance, Frequency	Temperature, DC Voltage / AC+DC, Current, Resistance, Frequency
Maximum Voltage	Up to 1000 V	Up to 1000 V
Bandwidth	100 kHz	100 kHz
Max Sampling Frequency	1 MHz (1 μs)	1 MHz (1 μs)
Internal Memory	500 GB	500 GB
Power analysis	✓ (Up to 4 simultaneous three-phased analysis and 1 kHz)	✓ (Up to 3 simultaneous three-phased analysis and 1 kHz)
Function of advanced mathematics	✓	✓
Remote control and process software	✓	✓
Interface	USB, Ethernet, Wi-Fi, Digital Input/Output	USB, Ethernet, Wi-Fi, Digital Input/Output
Detailed datasheet		

DAS1 700 / 8460





# ➤ TEMPERATURE DATALOGGERS

○ A compact unit with a programmable alarm function for long period measurements.



LOG1601



LOG1620

Model	LOG1601	LOG1620
Temperature Range	-40°C to +85°C	-40°C to 85°C
Humidity measurement	✘	✓
Integrated internal sensor	Resistive	Resistive
Resolution	0.1°C	0.1°C and 0.10%
Recording	50 000 points	50 000 points
Programmable alarm	✓	✓
Battery life	1 year	1 year
Supplied PC software	✓	✓
Interface	USB	USB
Detailed datasheet		





# TV METERS

An intuitive TV meters range dedicated to installers.



SEFRAM7817B



SEFRAM7848B



SEFRAM7849B



SEFRAM7859B

Model	SEFRAM7817B	SEFRAM7848B	SEFRAM7849B	SEFRAM7859B
DVB-T, DVB-T2, complete measurements	✓	✓	✓	✓
DVB-S, DVB-S2, DVB-S2X (option), complete measurements	✗	✓	✓	✓
DVB-C, DVB-C2, (J-83A), complete measurements	✓	✗	✓	✓
Satellite pointer mode	✗	✓	✓	✓
Terrestrial pointer mode	✓	✓	✓	✓
Digital SD/HD terrestrial bouquets visualisation	✓	✓	✓	✓
Digital SD/HD satellite bouquets visualisation	✗	✓	✓	✓
External power supply 5V/ 13V/ 18V/ 24V	✓	✓	✓	✓
Measurement plan	✗	✗	✓	✓
Values recording	✗	✗	✓	✓
Satellite and terrestrial reception optical measurement	✗	✗	✗	✓
Detailed datasheet				

7817B / 7848B / 7849B / 7859B





# TV METERS

A professional TV Meters range for broadcaster experts.



SEFRAM78804K



SEFRAM78814K



SEFRAM78824K



SEFRAM78854K

Model	SEFRAM78804K	SEFRAM78814K	SEFRAM78824K	SEFRAM78854K
DVB-T/T2/T2Lite, DVB-C/C2, DVB-S/S2 (MS)	✓	✓	✓	✓
MPEG-2, MPEG-4 (H.264) HEVC (H.265) decoding	✓	✓	✓	✓
Fast spectral analysis	✓	✓	✓	✓
DCSS, SatCR according to EN50607	✓	✓	✓	✓
Expert spectrum	✓	✓	✓	✓
2.4 GHz and 5 GHz WiFi	✓	✓	✓	✓
CAM CI	✗	✓	✓	✓
MER by CARRIER	✗	✓	✓	✓
IPTV	✗	✗	✓	✓
GPS	✗	✗	✗	✓
Detailed datasheet				

7880-4k / 7881-4k / 7882-4k / 7885-4k





# ➤ TRMS AC+DC MULTIMETERS

○ A complete range of high-accuracy handheld multimeters for demanding applications.



SEFRAM7334



SEFRAM7352B



SEFRAM7355

Model	SEFRAM7334	SEFRAM7352B	SEFRAM7355
Display	6000 points	40000 points	100000 points
Max DC Voltage / Max AC Voltage	1000 V	1000 V	1000 V
Max Voltage AC+DC	600 V	1000 V	1000 V
Max Current AC+DC	10 A	10 A	10 A
Max Resistance	40 MΩ	10 MΩ	10 MΩ
Continuity	✓	✓	✓
Capacitance measurement	✓	✓	✓
Bluetooth	✗	✓	✗
Detailed datasheet			



Test leads for multimeters



\*Compatible with SP296 current clamp  
30A/300A/3000A



7334 / 7335 / 7352B / 7355



## ➤ TRMS AC MULTIMETERS

○ An efficient range of multimeters.



SEFRAM7202



SEFRAM7203



SEFRAM7204



SEFRAM7220



SEFRAM7223

Model	SEFRAM7202	SEFRAM7203	SEFRAM7204	SEFRAM7220	SEFRAM7223
Display	6000 points				
Max DC Voltage / Max AC Voltage	600 V	600 V	600 V	1000 V	1000 V
Max DC Current / Max AC Current	×	10 A	10 A	×	10 A
Max Resistance	40 MΩ				
Continuity	✓	✓	✓	✓	✓
Capacitance measurement	✓	✓	✓	✓	✓
Temperature	×	×	✓	×	✓
Datalogger function	×	×	×	×	✓
Measurement voltage on solar panel (Option SA163)	×	×	×	×	✓
Detailed datasheet					



Test leads for multimeters



\*Compatible with SP296 current clamp  
30A/300A/3000A



7202 / 7203 / 7204 / 7220 / 7223





## ➤ CURRENT CLAMPS

Low-cost solutions offering value at best price-to-performance ratio.



BK312C



BK313C



MW3035



MW3027



\*Compatible with **SP296 current clamp**  
30A/300A/3000A



Model	BK312C	BK313C	MW3035	MW3027
Display	LCD 4000 points	LCD 6000 points	LCD 6000 points	LCD 2000 points
Max DC Voltage	600 V	600 V	1000 V	1000 V
Max AC Voltage	600 V	600 V	1000 V	1000 V
Max AC Current	400 A	600 A	100 A	200 A
Max DC current	×	600 A	100 A	×
Max resistance	400 Ω	1 MΩ	40 kΩ	10 kΩ
Jaw opening	25,4 mm	25 mm	20 mm	16 mm
Continuity	✓	✓	✓	✓
Detailed datasheet				



## ➤ CURRENT CLAMPS

○ Up to 1500 AAC/DC clamp-on meter range for maintenance services.



MW3360



MW3390



MW3366



\*Compatible with **SP296 current clamp**  
30A/300A/3000A



Model	MW3360	MW3390	MW3366
Display	LCD 4000 points	LCD 4000 points	LCD 6000 points
Max DC Voltage	600 V	1000 V	600 V
Max AC Voltage	600 V	750 V	600 V
Max AC Current	600 A (AC/DC)	1500 A	600 A (AC/DC)
Max Resistance	400 Ω	400 Ω	40 MΩ
Jaws opening	45 mm	53 mm	35 mm
Continuity	✓	✓	✓
Capacitance	✗	✗	2500 μF
Detailed datasheet			

MW3350 / MW3352 / MW3360 / MW3366 / MW3380 / MW3390





# SPECIALIZED CURRENT CLAMPS

Current clamps for dedicated applications.



MW3517BF



Photovoltaic measurement



MW3518



Flexible clamps with display



SP297B



Model	MW3517BF	MW3518	SP297B / SP298B
Display	LCD 6000 points	LCD 6000 points	LCD 10000 points
Max DC Voltage	1000 V / 2000 V with option SA163	1500 V	1000 V
Max AC Voltage	1000 V / 1500 V with option SA163	1000 V	1000 V
Max AC Current	600 A / 3000 A with option SP295	2000 A	3000 A
Max DC Current	600 A	2000 A	x
Max Resistance	600 kΩ	40 MΩ	10 kΩ
Jaw opening / diameter	42 mm	55 mm	100 mm / 160 mm
Double affichage	x	✓	✓
Detailed datasheet			

MW3517BF / MW3950B / SP297B-SP298B





## ➤ POWER METER CLAMPS

○ Up to 1000V / 1000kW Power Meter Clamps range made for maintenance services.



MW3526BF



MW3536BF

Model	MW3526BF	MW3536BF
Display	10000 points	10000 points
Max DC Voltage / Max AC Voltage	1000 V	1000 V
Max AC Current	600 A	1000 A
Max DC Current	600 A	1000 A
Max Resistance	100 MΩ	100 MΩ
Jaws opening	45 mm	45 mm
Active power measurement	✓	✓
Bluetooth	✓	✓
Detailed datasheet		

MW3526BF / MW3536BF





## VOLTAGE TESTERS

A complete range of LED voltage and continuity testers.



SEFRAM62



SEFRAM66



SEFRAM70

Model	SEFRAM62	SEFRAM66	SEFRAM70
Display	LED	LCD Screen + LED	LCD Screen + LED
IP2X Touch points	✓	✓	✓
Max AC Voltage	690 V	1000 V	1000 V
Max DC Voltage	690 V	1500 V	1000 V
Continuity test	✓	✓	✓
Resistance measurement	✓	✓	✓
Phases rotation test	✓	✓	✓
Current measurement	✗	✗	200 A AC
Detailed datasheet			





## ➤ INSULATION TESTERS

50V to 1000V Insulation tester, 600V TRMS Multimeter.

New

Active testing probe for MW9090 and MW9091 : 9090PROBE



MW9090



MW9091



MW9092

Model	MW9090	MW9091	MW9092
Testing Voltage	50 V, 100 V, 250 V, 500 V, 1000 V	50 V, 100 V, 250 V, 500 V, 1000 V	50 V, 100 V, 250 V, 500 V, 1000 V
Insulation resistance measurement	20 GΩ	22 GΩ	20 GΩ
Continuity test	✓	✓	✓
PI and DAR measurement	✓	✓	✓
Multimeter function	✗	✓	✓
Deported probe	✓	✓	✗
Detailed datasheet			





## EARTH TESTERS

A complete range of earth testers



New

MW9325



MW9452D

Model	MW9325	MW9452D
Earth impedance testing with rods	✗	✓
Earth loop impedance testing	✓	✗
RCD testing	✓	✓
Harmonics measurements	✓	✗
Measurements saving	✓	✗
Interface	Mobile application	✗
Detailed datasheet		





## CABLE TRACERS

A complete range of cable tracers



SEFRAM95



SEFRAM96



SEFRAM97



MW9520

Model	SEFRAM95	SEFRAM96	SEFRAM97	MW9520
Cables under voltage testing	x	x	x	✓
Tracer function	x	✓	✓	✓
Pins cable testing	✓	✓	x	x
Electric cables types	RJ45/ RJ11/BNC	RJ45/ RJ11/BNC/USB power line	RJ45/ RJ11/BNC/USB power line	RJ45/ RJ11/BNC/USB power line
Analog phone lines testing	✓	x	x	x
Non electric cables testing	x	x	x	✓
Detailed datasheet				





## ENVIRONMENT TESTERS

A multi-purpose range for your environment measurements.



### SEFRAM9822B

#### Thermo-hygrometer

- Humidity 0 to 100%
- Temperature probe T1: -20°C to 60°C
- Thermocouple Temperature probe T2: -200°C to 1370°C
- USB interface with software
- Recording 32000 points
- Bluetooth application

Detailed datasheet



### SEFRAM9836

#### Sound level meter with recording

- Measuring range 30 dB to 130 dB
- Frequency weighting A and C
- USB interface with software
- Recording 128000 points
- MP3 audio recording
- No data logging version : SEFRAM9835

Detailed datasheet



### SEFRAM9862

#### Hot wire anemometer

- Air speed and flow measurement
- Temperature measurement
- Humidity measurement

Detailed datasheet



### SEFRAM9816B

#### 4 inputs thermometer

- Measurement range -200 °C to 1370 °C
- USB interface with software
- Recording 32000 points
- Bluetooth application

Detailed datasheet



### SEFRAM9855

#### Digital light meter

- Measuring range 40 to 4000 lux
- Incandescent light, natural LED
- Min, Max, Avg, Hold functions

Detailed datasheet



### SEFRAM 9861

#### Moisture meter

- Bargraph with 48 LED
- Sturdy and durable moisture probe
- Analog output for recording data

Detailed datasheet





# ➤ ENVIRONMENT TESTERS

○ A range dedicated to thermography cameras for preventive maintenance



## SEFRAM 9831

Handheld Thermography Camera

- Laser light
- Thermography range -20°C to 550°C
- Resolution 160 x 120 (19200 pixels)
- Thermal snapshots (8GB SD card)
- PC software for analysis and test reports

*Detailed datasheet*



## SEFRAM 9832

**Thermography Camera High Resolution**

- Thermography range -20 to 550°C
- Resolution 256 x 192 (49152 pixels)
- Thermal and optical snapshot (16GB SD card)
- PC software for analysis and test reports
- Mobile application

*Detailed datasheet*



## SEFRAM 9833

**Thermography Camera Pocket Format**

- Temperature range -20 to 400°C
- Resolution 256 x 192 (49 152 pixels)
- Thermal and optical snapshot (16GB SD card)
- Video recording
- PC software for analysis and test reports
- Mobile application

*Detailed datasheet*





## ➤ ENVIRONMENT TESTERS

○ A range dedicated to gas detection



### Datalogger, carbon dioxide meter (CO<sub>2</sub>)

- CO<sub>2</sub>, temperature and humidity measurement
- Alarm with buzzer for CO<sub>2</sub>
- 32 000 points datalogging
- USB interface with software provided

*Detailed datasheet*



SEFRAM 9825



### Refrigerant gas leak detector

- Heated semiconductor gas sensor
- LED tri-colored leak level indicator
- Battery life: 12 hours
- 40 cm flexible probe

*Detailed datasheet*



SEFRAM 9891



### Carbon monoxide meter (CO)

- CO and temperature measurement
- Alarm with buzzer for CO
- MAX and HOLD data function
- Auto Power Off

*Detailed datasheet*



SEFRAM 9893



### Combustible gas leak detector

- Gasoline, propane, natural gas or fuel oil detection
- LED tri-colored leak level indicator
- Autonomie 40 heures
- 40 cm flexible stainless probe

*Detailed datasheet*



SEFRAM 9892



# ➤ DC POWER SUPPLIES

○ A triple output DC power supplies range up to 375W.



BK1672



BK1673



BK1761



BK1762

Model	BK1672	BK1673	BK1761	BK1762
Power	200W	375W	220W	300W
Outputs	3	3	3	3
Output Voltage	2x 0-32V / 1x 5V	2x 0-32V / 1x 5V	2x 0-35V / 1x 2 -6.5V	2x 0-60V / 1x 4-6.5V
Output Current	2x 0-3A / 1x 3A	2x 0-6A / 1x 3A	2x 0-3A / 1x 0-5A	2X 0-2A / 1x 0-5A
CC and CV mode	✓	✓	✓	✓
Serial or parallel mode	✓	✓	✓	✓
Protection	✗	✗	OVP	OVP
Interface	✗	✗	✗	✗
Remote sense	✗	✗	✗	✗
Detailed datasheet				

BK1672 / BK1673 / BK1761 / BK1762





# ➤ DC POWER SUPPLIES

○ A switching power supplies range up to 960W.



BK168XB series



BK169XB series



BK190XB series

Model	BK168XB series	BK169XB series	BK190XB series
Power	From 300 to 360W	200W	From 900W to 960W
Outputs	1	1	1 (+ 1 auxiliary output)
Output Voltage	Up to 60V	Up to 60V	Up to 60V
Output Current	Up to 20A	Up to 10A	Up to 60A
CC and CV mode	✓	✓	✓
Remote control software	✓	✓	✓
Protection	OCP, OVP, OTP	OCP, OVP, OTP	OCP, OVP, OTP
Interface	USB	USB, RS 485	USB
Remote sense	✗	✗	✗
Analogue control	✓	✗	✓
Detailed datasheet			

BK168XB / BK169XB / BK190XB





# ➤ DC POWER SUPPLIES

○ A programmable multi-range linear power supplies.



BK910X series



BK920XB series



BK914X series

Model	BK910X series	BK920X series	BK914X series
Power	320W	From 200W to 600W	300W
Outputs	1	1 (+ 1 auxiliary output)	3
Output Voltage	Up to 84V	Up to 84V	Up to 60V
Output Current	Up to 20A	Up to 25A	Up to 8A
CC and CV mode	✓	✓	✓
Remote control software	✓	✓	✓
Protection	OCP, OVP, OTP	OCP, OVP, OTP	OCP, OVP, OTP
Interface	USB	USB, RS232, Driver LabView	USB, LAN(LXI), GPIB(option), logics I/O, LabView and IVI.NET drivers
Batteries test	✗	✓	✗
Remote sense	✓	✓	✓
Analogue control	✓	✓	✗
Detailed datasheet			





# ➤ DC POWER SUPPLIES

○ A programmable dual range linear power supplies range with a configurable interface.



BK917XB series



BK918XB series

Model	BK917XB series	BK18XB series
Power	From 100W to 210W	From 200W to 600W
Outputs	2	1
Output voltage	Up to 70V	Up to 600V
Output current	Up to 5A	Up to 10A
LED testing mode	✓	✓
Standard interface	USB, Driver LabView	USB, Driver LabView
Flexible interface according to the chosen card option	RS-232, LAN + IEE, Analogue, RS485	RS-232, LAN + IEE, Analogue, RS485
Remote control software	✓	✓
Remote sense	✓	✓
Protection	OCP, OVP	OCP, OVP
Detailed datasheet		





# ➤ DC POWER SUPPLIES

○ A wide range of rackable programmable linear Power Supplies.



BK911X/B series



XLN series High Voltage



XLN series High Current

Model	BK9115 series	XLN series High Voltage	XLN series High Intensity
Power	From 1200W to 3000W	1560W	1440W
Outputs	1	1	1 (+ 1 auxiliary output 5V/1A)
Output Voltage	Up to 150V	Up to 600V	Up to 100V
Output Current	Up to 120A	Up to 10.4A	Up to 24A
Serial or parallel mode	✓	✓	✓
Interface	USB, RS-232, RS-485, LAN, GPIB (depending on model)	USB, RS-485, Driver LabView (GPIB, LAN in option)	USB, RS-485, Driver LabView (GPIB, LAN in option)
Analogue control	✓	✓	✓
Remote sense	✓	✓	✓
Protection	OVP, OVP, OTP	OVP,OCP,OTP, OPP	OVP,OCP,OTP, OPP
Detailed datasheet			





# ➤ DC POWER SUPPLIES

○ A wide range of rackable programmable linear Power Supplies including photovoltaic features.



MR series



PVS series

Model	MR series	PVS series
Power	Up to 5000W	From 3000W to 5100W
Outputs	1	1
Output Voltage	Up to 1000V	Up to 1000V
Output Current	Up to 80A	Up to 8.5A
Serial or parallel mode	✓	✓
Interface	USB, RS-232, GPIB, LAN (LXI)	USB, RS-485, RS-232, IEEE, LAN, Driver LabView
Analogue control	✓	✓
Remote sense	✓	✓
Protection	OCP, OVP, OTP, OPP	OVP, OVP, OTP, OPP
Detailed datasheet		





# ➤ AC POWER SOURCES

Programmable AC Power Sources range from 300 VA to 1500 VA.



BK9801



BK9803/B



BK9805/B

Model	BK9801	BK9803/B	BK9805/B
Power	300 VA	750 VA	1500 VA
Outputs	1	2	1
Output Voltage	Up to 300V	Up to 300V	Up to 300V
Output Current	Up to 3A	Up to 6A	Up to 12A
Output frequency	45 to 500Hz	45 to 500Hz	45 to 500Hz
Remote control Software	✓	✓	✓
External trigger	✓	✓	✓
Interface	USB, LAN, RS-232, LabView Driver	USB, LAN, RS-232, LabView Driver, GPIB (depending on model)	USB, LAN, RS-232, LabView Driver, GPIB (depending on model)
Rack-mount	✓	✓	✓
Protection	OCP, OVP, OPP, OTP	OCP, OVP, OPP, OTP	OCP, OVP, OPP, OTP
Detailed datasheet			

BK9801 / BK9803 / BK9805





# ➤ AC+DC POWER SOURCES

Programmable AC Power Sources up to 3000 VA with DC output.



3-Phase capability using 3 AC sources and the 3-Phase kit TL983P-KIT



BK9832B



BK9833B

Model	BK9832	BK9833
AC power	2000 VA	3000 VA
DC power	1000 W	1500 W
Outputs	1	1
Output Voltage	Up to 300V	Up to 300V
Output Current	Up to 20A	Up to 30A
Output frequency	From 45 to 1200Hz (single phase) / From 45 to 600 Hz (Three-phase)	From 45 to 1200Hz (single phase) / From 45 to 600 Hz (Three-phase)
Remote control Software	✓	✓
External trigger	✓	✓
Interface	USB, RS-232, RS-232, LabView Driver	USB, LAN, RS-232, GPIB, LabView Driver
Rack-mount	✓	✓
Protection	OCP, OVP, OPP, OTP	OCP, OVP, OPP, OTP

Detailed datasheet





# ➤ DC ELECTRONIC LOADS

○ An Electronic Loads range from 150W to 1500W.



BK8540



BK8500B

Model	BK8540	BK8500B
Max power	150W	Up to 1500W
Inputs	1	1
Input voltage	150V	Up to 500V
Input current	30A	Up to 240A
Constant mode	CC, CV, CR	CC, CV, CR, CW
Interface	USB (TTL)	USB (TTL)
Analogue control	✗	✓
Batteries test	✗	✓
Remote sense	✗	✓
Protection	OVP, OCP	OVP,OCP,OTP, OPP
Detailed datasheet		

BK8540 /BK8500B





# ➤ DC ELECTRONIC LOADS

○ A high performance Electronic Loads range up to 1500W.



BK8600



BK8601



BK8602/B



BK8610/B



BK8612/B

Model	BK8600	BK8601	BK8602/B	BK8610/B	BK8612/B
Max power	150W	250W	200W	750W	1500W
Inputs	1	1	1	1	1
Input voltage	120V	120V	500V	120V	500V
Input current	30A	60A	15A	120A	30A
Constant mode	CC, CV, CR, CW	CC, CV, CR, CW	CC, CV, CR, CW	CC, CV, CR, CW	CC, CV, CR, CW
Interface	USB, RS-232, GPIB	USB, RS-232, GPIB	USB, RS-232, GPIB (depending on model)	USB, RS-232, GPIB (depending on model)	USB, RS-232, GPIB (depending on model)
Analogue control	✓	✓	✓	✓	✓
Remote sense	✓	✓	✓	✓	✓
Battery test	✓	✓	✓	✓	✓
Protection	OVP, OCP, OPP, OTP	OVP,OCP,OTP, OPP	OVP,OCP,OTP, OPP	OVP, OCP, OTP, OPP	OVP, OCP, OTP, OPP
Detailed datasheet					

BK8600 / BK8601 / BK8602 / BK8610 / BK8612





# ➤ DC ELECTRONIC LOADS

○ A high performance Electronic Loads range from 1500W to 6000W.



BK8614/B



BK8616



BK8620



BK8622



BK8624



BK8625

Model	BK8614/B	BK8616	BK8620	BK8622	BK8624	BK8625
Max power	1500W	1200W	3000W	2500W	4500W	6000W
Inputs	1	1	1	1	1	1
Input voltage	120V	500V	120V	500V	120V	120V
Input current	240A	60A	480A	100A	600A	720A
Constant mode	CC, CV, CR, CW	CC, CV, CR, CW	CC, CV, CR, CW	CC, CV, CR, CW	CC, CV, CR, CW	CC, CV, CR, CW
Interface	USB, RS-232, GPIB (depending on model)	USB, RS-232, GPIB				
Analogue control	✓	✓	✓	✓	✓	✓
Remote sense	✓	✓	✓	✓	✓	✓
Battery test	✓	✓	✓	✓	✓	✓
Protection	OVP, OCP, OPP, OTP	OVP, OCP, OTP, OPP				
Detailed datasheet						

BK8614 / BK8616 / BK8620 / BK8622 / BK8624 / BK8625





# ➤ DC ELECTRONIC LOADS

○ A modular\* Electronic Loads range from 200W to 2400W.



MDL4U series

Model	MDL4U200	MDL4U252	MDL4U302	MDL4U305	MDL4U400	MDL4U505	MDL4U600
Max power	200W	250W / 50W	300W / 300W	300W	400W	500W	600W
Inputs	1	2	2	1	1	1	1
Input voltage	80V						
Input current	40A	20A	45A	20A	60A	30A	120A
Interface	USB, RS-232, GPIB, LAN						
Constant mode	CC, CV, CR, CW, CZ						
Analogue control	✓	✓	✓	✓	✓	✓	✓
Remote sense	✓	✓	✓	✓	✓	✓	✓
Protection	OVP, OCP, OPP, OTP	OVP, OCP, OTP, OPP					
Detailed datasheet							

\*To be integrated in the MDL4U002 expansion unit for rack-mount





# ➤ LCR METERS

○ A high resolution bench LCR meters up to 1MHz.



BK891



BK894



BK895

Model	BK891	BK894	BK895
Measurement	R, L, C, Z, D, Q, G, B, Y, ESR, DCR, $\theta$	R, L, C, Z, D, Q, G, B, Y, ESR, DCR, $\theta$	R, L, C, Z, D, Q, G, B, Y, ESR, DCR, $\theta$
Test frequency	20 Hz to 300kHz	20Hz to 500kHz	20Hz to 1MHz
Basic accuracy	0.05%	0.05%	0.05%
Frequency scanning function	✓	✓	✓
Memory function	100 configurations	40 configurations	40 configurations
Interface	USB, LAN, RS-232, GPIB	USB, LAN, RS-232, GPIB	USB, LAN, RS-232, GPIB
Transformer test	✗	✓ (option)	✓ (option)
Detailed datasheet			





## ➤ LCR METERS

○ 40,000-count handheld LCR meters range.



BK878B



BK879B



BK880

Model	BK878B	BK879B	BK880
Measurement	R, L, C, D, Q	R, L, C, Z, D, Q, ESR, $\theta$	R, L, C, Z, D, Q, ESR, DCR, $\theta$
Test frequency	120Hz, 1kHz	100Hz, 120 Hz, 1KHz, 10kHz	100Hz, 120Hz, 1KHz, 10kHz, 100kHz
Basic accuracy	0.5%	0.5%	0.1%
Automatic range change	✓	✓	✓
Min/Max/AV Hold function	✓	✓	✓
Interface	USB	USB	USB
Detailed datasheet			





# BENCH MULTIMETERS

High resolution True RMS Bench Digital Multimeters.



BK2831E



BK5491B



BK5492C/BK5493C

BK2831E / BK5491B / BK5492C / BK5493C

Model	BK2831E	BK5491B	BK5492C / BK5492CGPIB	BK5493C / BK5493CGPIB
Measurements	TRMS AC + DC Voltage and Current, Frequency, Period, Resistance	TRMS AC + DC Voltage and Current, Frequency, Period, Resistance	TRMS AC+DC Voltage and Current, Frequency, Resistance, Capacitance, temperature	TRMS AC+DC Voltage and Current, Frequency, Resistance, Capacitance, temperature
Number of points	20,000 points	50,000 points	120,000 points	1,200 000 points
Basic accuracy	0.03%	0.02%	0.01%	0,0035 %
Voltage	750V AC - 1000V DC	750V AC - 1000V DC	750V AC - 1000V DC	750V AC - 1000V DC
Current	20A AC+DC	20A AC+DC	12A AC+DC	10A AC+DC
Bandwidth	100 kHz	100 kHz	100 kHz	300 kHz
Interface	USB	USB, RS-232	USB, RS-232, LAN, GPIB (factory option)	USB, RS-232, LAN, GPIB (factory option)
Remote control software	✓	✓	✓	✓
Detailed datasheet				





# FUNCTIONS GENERATORS

DDS Dual Channel Function/Arbitrary Waveform Generators up to 60MHz.



BK405XB series

Model	BK4053B	BK4054B	BK4055B
Frequency range	1 $\mu$ Hz - 10MHz	1 $\mu$ Hz - 30MHz	1 $\mu$ Hz - 60MHz
Number of channels	2	2	2
Sampling speed	150 MSa/s	150 MSa/s	150 MSa/s
Generated signals	Sine, ramp, pulse, arbitrary	Sine, ramp, pulse, arbitrary	Sine, ramp, pulse, arbitrary
Modulation	AM/DSB-AM/ASK/FM/FSK/PM/PWM/External	AM/DSB-AM/ASK/FM/FSK/PM/PWM/External	AM/DSB-AM/ASK/FM/FSK/PM/PWM/External
Internal/External trigger	✓	✓	✓
Interface	USB, LAN, IEEE (option)	USB, LAN, IEEE (option)	USB, LAN, IEEE (option)
Remote control software	✓	✓	✓
Detailed datasheet			





# FUNCTIONS GENERATORS

DDS Dual Channel Function/Arbitrary Waveform Generators up to 120MHz.



BK406XB series

Model	BK4062B	BK4063B	BK4064B
Frequency range	1 $\mu$ Hz - 40MHz	1 $\mu$ Hz - 80MHz	1 $\mu$ Hz - 120MHz
Number of channels	2	2	2
Sampling speed	300 MSa/s (DDS) / 75 MSa/s (True arbitrary)	300 MSa/s (DDS) / 75 MSa/s (True arbitrary)	300 MSa/s (DDS) / 75 MSa/s (True arbitrary)
Generated signals	Sine, ramp, pulse, arbitrary	Sine, ramp, pulse, arbitrary	Sine, ramp, pulse, arbitrary
Modulation	AM/DSB-AM/ASK/FM/FSK/PM/PWM/External	AM/DSB-AM/ASK/FM/FSK/PM/PWM/External	AM/DSB-AM/ASK/FM/FSK/PM/PWM/External
Internal/External trigger	✓	✓	✓
Interface	USB, LAN, IEEE (option)	USB, LAN, IEEE (option)	USB, LAN, IEEE (option)
Remote control software	✓	✓	✓
Detailed datasheet			





# PULSE GENERATORS

High performance programmable pulse generators range.



BK4033



BK4034

Model	BK4033	BK4034
Generated signals	Pulse	Pulse
Number of channels	1	2
Pulse length	From 10ns to 10s	From 10ns to 10s
Output frequency	From 0.1Hz to 50MHz	From 0.1Hz to 50MHz
Internal/External trigger	✓	✓
Interface	IEEE, RS-232	IEEE, RS-232
Detailed datasheet		


BK4003 / BK4034






# DIGITAL OSCILLOSCOPES

A performance and value all in one Digital Storage.



BK2190E



BK2194



BK2560B Series

Model	BK2190E	BK2194	BK2560B Series
Bandwidth	100MHz	100MHz	Up to 350MHz
Number of channels	2	4	4
Sampling rate	1GSa/s	1GSa/s	2GSa/s
Remote control software	✓		✓
MSO option (when rotating)	✗	✗	✓
Interface	LAN, USB	LAN, USB	LAN, USB
Detailed datasheet			





# SPECTRUM ANALYZERS

Range of spectrum analyzers delivers performance and functionality in frequency ranges from 9 kHz to 3.2 GHz.



BK2682



BK2683

Model	BK2682	BK2683
Frequency range	9kHz – 2.1GHz	9kHz – 3.2GHz
Minimal resolution bandwidth	1Hz	1Hz
Sensitivity	- 161dBm/Hz	- 161dBm/Hz
Preamplifier	✓	✓
Pursuit generator	✓	✓
External software	✓	✓
Interface	LAN, USB	LAN, USB
Detailed datasheet		





# ➤ RF POWER METERS

○ High performance benchtop RF power meters.



RFM3002\*



RFM3004\*

Model	RFM3002	RFM3004
Number of channels	2 channels	4 channels
Independent or synchronous multi-channel measurements	✓	✓
Trigger synchronization	✓	✓
Display 16 common power measurements	✓	✓
Supports SCPI-1999.0	✓	✓
Interface	LAN, USB, GPIB(option), HDMI	LAN, USB, GPIB(option), HDMI
Detailed datasheet		

\*Compatible with RFP3000 Series USB RF Peak Power Sensors.

RF POWER METER RFM3002-RFM3004





# ➤ USB RF Peak Power Sensors

○ The RFP3000 Series RF Peak Power Sensors are the performance leaders in the peak power measurement.



RFP3000 Series\*

USB RF PEAK POWER SENSORS RFP3000 SERIES

Model	RFP3006	RFP3008	RFP3018	RFP3118	RFP3040	RFP1340
Real-time Power Processing™ Technology	✓	✓	✓	✓	✓	✓
RF Frequency Range	50 MHz to 6 GHz	50 MHz to 8 GHz	50 MHz to 18 GHz	50 MHz to 18 GHz	50 MHz to 40 GHz	50 MHz to 40 GHz
Video bandwidth (high/std)	195 MHz / 350 kHz	165 MHz / 350 kHz	70 MHz / 350 kHz	6 MHz / 350 kHz	70 MHz / 350 kHz	6 MHz / 350 kHz
Superior 100 ps time base resolution	✓	✓	✓	✓	✓	✓
Acquisition rate up to 100 MSPS	✓	✓	✓	✓	✓	✓
Power Analyzer software	✓	✓	✓	✓	✓	✓
Detailed datasheet						

\*Compatible with RFM3000 Series RF Power Meters.





# BATTERY CAPACITY ANALYZERS

A handheld battery capacity analyzer to test and maintain sealed lead acid (SLA) batteries.



BK600B



BK601B



BK603B

Model	BK600B	BK601B	BK603B
Supported SLA battery voltages	12V	6V / 12V	6V / 12V
Capacity measurement	Up to 100Ah	Up to 100Ah	Up to 100Ah
Internal resistance measurement	✗	✗	✓
Resolution	10mV	10mV	10mV
Recording mode	✗	✗	✓
Interface	✗	✗	USB
Detailed datasheet			

BK600B / BK601B / BK603B





# BATTERY ANALYZERS

A bench battery analyzer range up to 300V battery packs.



BA6010



BA6011

Model	BA6010	BA6011
Voltage measurement range	6V / 60V	30V / 300V
Accuracy	0.05%	0.05%
AC test signal	1kHz	1kHz
Resolution	100µV	1mV
Interface	RS-232, USB, Analogue	RS-232, USB, Analogue
Detailed datasheet		





## ➤ SEFRAM SALESMEN : EMEA AREA

Your contacts



EMEA AREA

**Sales Director**

Francisco Castro

Tél: +33.7.84.35.65.75

Mail: castro@sefram.com

Mario Abboud

Tél: +33.6.38.40.77.60

Mail: abboud@sefram.com

Frédéric Lalier


Tél: +33.6.12.32.25.85

Mail: lalier@sefram.com

Florian Arnaud

Tél: +33.6.17.15.09.59

Mail: arnaud@sefram.com



✓ Europe

✓ Middle-East

✓ Africa






## ➤ OTHER CATALOGS

*Testing accessories catalog*



*Oscilloscopes probes catalog*




*B&K PRECISION catalog*



*Data Acquisition Solutions catalog*



*TV meters catalog*





# ➤ OUR CONTACTS



## Postal address

- 32 rue Edouard Martel BP 55
- 42009 SAINT-ETIENNE
- Cedex 2 FRANCE

## Customer service

- Phone: +33 (0)4 77 59 36 91
- Phone: +33 (0)4 77 59 36 96
- E-mail : [services@sefram.com](mailto:services@sefram.com)

## Reception and Sales department

- Phone: +33 (0)4 77 59 01 01 (reception)
- Phone: +33 (0)4 77 59 36 80
- Phone: +33 (0)4 77 59 36 81
- Web: [www.sefram.com](http://www.sefram.com)
- E-mail : [sales@sefram.com](mailto:sales@sefram.com)

## Technical support

- Phone: +33 (0)4 77 59 01 01
- E-mail : [support@sefram.com](mailto:support@sefram.com)

